

# TECHNICAL DATASHEET

## PR – 20 (PVC LUBRICANT)

### GENERAL DATA

COMPOSITION	WAX BASED – ONE PACK
APPEARENCE	GRANULES
COLOUR	WHITE TO OFF-WHITE
CONGEALING POINT, °C	105 °C ± 5 °C
PENETRATION	MAX. 10MM
SHELF LIFE	1 YEAR

### APPLICATIONS

**PR-20** is a Lubricant for Rigid PVC Pipes and Fitting.

### DOSAGE

Recommended use: 1.2 – 2 phr.

### PERFOMANCE

**PR-20** is a wax based ONE PACK Lubricant for RIGID PVC PIPES and FITTINGS AND PVC PROFILES.

### PACKAGING, STORAGE & HANDALING

**PR-20** is supplied in bags of net weight 25Kgs. Storage at room temperature is recommended. Once opened, bags should be firmly closed after use. should be stored indoor and in a dry place, keep away from water, and avoid direct contact with air and direct sunlight.

DISCLAIMER: -Typical values are representative of production and may vary from time to time. All information to the best of our knowledge and belief is accurate and reliable as on the date of compilation. Moreover, no warranty or guarantee is made as to the accuracy, reliability or completeness nor do we offer any warrant against patent infringement. It is the user's responsibility to ascertain the suitability of this information for his or her use. Sampling and Testing procedures in effect at the time of production will be used for certification and we reserve the right to use any test method in certifying the material.